AC Adapter ADC-1430S

The ADC-1430S supplies required DC power exclusively for SUMITOMO Fusion Splicers.

The ADC-1430S is supplied with TYPE-71, 81, Q101 series

and T-55 as a standard package.

SUMITOMO ELECTRIC



| Specifications | | | | | |
|---------------------------|-------------------|--|--|--|--|
| AC power supply | AC input (rated) | 100 to 240V AC, 50 to 60Hz | | | |
| | DC output (rated) | 14V, 5.71A | | | |
| Applicable fusion splicer | | TYPE-71 series, TYPE-81 series, TYPE-Q101 series and T-55 | | | |
| DC cord length | | Approx. 1.2m | | | |
| Dimensions and Weight | | 76(W) x 146(L) x 43(H) mm without any cords, Approx. 600g | | | |
| AC power cord (Option) | | SUMITOMO's AC power cords : PC-AC2 (American type), PC-AC3 (CEE type), PC-AC4 (Japan type), PC-AC5 (British type), PC-AC6 (Oceania type), PC-AC7 (South African type), PC-AC8 (China type), PC-AC9(India type) | | | |
| Country of origin | | Taiwan | | | |

| AC power cord (Option) | | | | | | | | | |
|------------------------|----------|----------|--------|--------|--------|--------|--------|--|--|
| Part No. | PC-AC2/4 | PC-AC3 | PC-AC5 | PC-AC6 | PC-AC7 | PC-AC8 | PC-AC9 | | |
| Appearance of plug-end | | | | | Co.C | È | Co.Co | | |
| IEC plug type | TYPE B | TYPE E&F | TYPE G | TYPE I | TYPE M | TYPE I | TYPE D | | |
| Cord length | 3m | 3m | 2m | 2m | 2.5m | 3m | 1.8m | | |



©2015 Sumitomo Electric Industries, Ltd. All Rights Reserved

Specifications are subject to change without prior notice.